








	Product	Description
	<b>Positive Locking System</b>	<ul style="list-style-type: none"> <li>• Current rating: 10.0A</li> <li>• Wire Gauge: 12-30 AWG</li> <li>• Voltage rating: 300V</li> <li>• Circuits: 2-24</li> <li>• Pitch: 4.00 - 5.00mm (.155-.200")</li> <li>• Operating temperature: -40 to +115°C</li> <li>• UL File No.: E48521</li> </ul>
	<b>Beau™ EuroMate™ Pluggable</b>	<ul style="list-style-type: none"> <li>• Current rating: 12.0-15.0A</li> <li>• Wire Gauge: 12-22 AWG</li> <li>• Voltage rating: 300V</li> <li>• Circuits: 3-24</li> <li>• Pitch: 3.81-5.08mm (.150-.200")</li> <li>• Operating temperature: -40 to +120°C</li> <li>• UL File No.: E48521</li> </ul>
	<b>Beau™ Eurostyle™ High-Power Fixed Mount</b>	<ul style="list-style-type: none"> <li>• Current rating: 20.0-115.0A</li> <li>• Wire Gauge: 1-30 AWG</li> <li>• Voltage rating: 300V or 600V</li> <li>• Circuits: 2-16</li> <li>• Pitch: 5.08-15.00mm (.200-.591")</li> <li>• Operating temperature: -40 to +130°C</li> <li>• UL File No.: E48521</li> </ul>
	<b>EuroMax™ Pluggable High-Power</b>	<ul style="list-style-type: none"> <li>• Current rating: 85.0A</li> <li>• Wire Gauge: 3-14 AWG</li> <li>• Voltage rating: 600V</li> <li>• Circuits: 2-12</li> <li>• Pitch: 12.00mm (.472")</li> <li>• Operating temperature: -40 to +130°C</li> <li>• UL File No.: E48521</li> </ul>

	Product	Description
	<b>Eurostyle™ Two-Screw Terminal Strips</b>	<ul style="list-style-type: none"> <li>• Current rating: 20.0-63.0A</li> <li>• Wire Gauge: 6-22 AWG</li> <li>• Voltage rating: 300V or 600V</li> <li>• Circuits: 2-12</li> <li>• Pitch: 8.00-15.00mm (.315-.591")</li> <li>• Operating temperature: -40 to +105 Deg. C</li> <li>• UL File No.: E48521</li> </ul>
	<b>Eurostyle™ PCB Pluggable</b>	<ul style="list-style-type: none"> <li>• Current rating: 8.0A-30.0A</li> <li>• Wire Gauge: 12-30 AWG</li> <li>• Voltage rating: 300V</li> <li>• Circuits: 2-48</li> <li>• Pitch: 3.50-9.53mm (.138-.375")</li> <li>• Operating temperature: -40 to +115°C</li> <li>• UL File No.: E48521</li> </ul>
	<b>Beau™ Barrier Strips</b>	<ul style="list-style-type: none"> <li>• Current rating: 10.0-65.0A</li> <li>• Wire Gauge: 8-30 AWG</li> <li>• Voltage rating: 300V or 600V</li> <li>• Circuits: 2-32</li> <li>• Pitch: 6.37-17.48mm (.250-.688")</li> <li>• Operating temperature: -40°C to +130°C</li> <li>• UL File No.: E48521</li> </ul>